

What is Claimed is:

1. A dry solid particle mixture for equalizing radial and lateral force variations at the tire/road footprint of a pneumatic tire, wherein
 - (a) the particles forming said particle mixture are freely flowable and non-tacky at elevated temperatures;
 - (b) said particle mixture is essentially devoid of liquid material;
 - (c) said particle mixture comprises a plurality of sets of particles, wherein each set consists essentially of particles of a predetermined size or size range; and
 - (d) said particle mixture exhibits a multimodal particle size distribution.
- 10 2. A particle mixture according to claim 1, wherein said particle mixture comprises spheres of a first diameter and spheres of a second diameter.
3. A particle mixture according to claim 1, wherein said particle mixture comprises a first set of particles having a first size range and a second set of particles having a second size range, the particle size distribution of said particle mixture being characterized by at least two peaks.
- 15 4. A particle mixture according to claim 1, wherein said particle mixture comprises a first set of particles having a first size range, a second set of particles having a second size range, a third set of particles having a third size range, wherein the particle sizes ranges do not overlap.
- 20 5. A particle mixture according to claim 1, wherein said particles forming said particle mixture have a specific gravity greater than 1.
6. A particle mixture according to claim 1, wherein said particles forming said particle mixture have sufficient hardness to prevent them from degrading while tumbling in said tire.
- 25 7. The particle mixture according to claim 1, wherein said mixture comprises polymeric resin particles.
8. The particle mixture according to claim 7, wherein said particle mixture includes substantially 70% by weight of said polymeric resin and 28% by weight of a cellulose material.
- 30 9. The particle mixture according to claim 7, wherein said polymeric resin is a thermoset material.
10. The particle mixture according to claim 7, wherein said polymeric resin is a

PCT/US00/12896

thermoplastic material.

11. The particle mixture according to claim 1, wherein one set of particles is made of fiberglass.
12. A particle mixture according to claim 11, wherein said fiberglass particles are in a size range substantially between 130-200 U.S. screen size.
13. A particle mixture according to claim 1, further comprising a lubricant material.
14. A particle mixture according to claim 13, wherein said lubricant particles are in a size range substantially between 200-325 U.S. screen size.
15. A particle mixture according to claim 13, wherein said particle mixture comprises 10 15-30 % lubricant material by weight.
16. A particle mixture according to claim 13, wherein said lubricant is talc.
17. A particle mixture according to claim 13, wherein said lubricant is corn starch.
18. A particle mixture according to claim 13, wherein said lubricant is an anti-agglomeration agent.
- 15 19. A particle mixture according to claim 1, wherein the mixture exhibits a multimodal particle size characteristic when plotted on a particle weight percentage versus particle size diameter basis.
20. A particle mixture according to claim 1, wherein said particles are in a size range substantially between 60-270 U.S. screen size.